


# SQR-SD4N

## SODIMM DDR4 2666

# SQR-SD4N

## SODIMM DDR4 3200

NEW



RoHS  
2002/95/EC  
CE FCC

### Features

- JEDEC standard 260-pin SODIMM
- Data transfer rate 2666 MT/s
- FIXED BOM
- Original Samsung adopted
- DRAM dynamic monitoring software support


### Specifications

Category	DDR4
Clock Speed	2666 MHz
Voltage	1.2V
Pins/DIMM	260-pin SODIMM
Gold Plating on PCB	30u"
Operating Temperature	0 ~ 85 °C
Dimensions (mm)	69.6 x 30 ± 0.13

### Ordering Information

PN	Description
SQR-SD4N2G2K6SNXFB	260pin SODIMM DDR4 2666 2GB 1.2v 256x16 (0 ~ 85 °C) SAM
SQR-SD4N4G2K6SNPCB	260pin SODIMM DDR4 2666 4GB 1.2v 512x16 (0 ~ 85 °C) SAM
SQR-SD4N4G2K6SNEFB	260pin SODIMM DDR4 2666 4GB 1.2v 512Mx8 (0 ~ 85 °C) SAM
SQR-SD4N8G2K6SNBCB	260pin SODIMM DDR4 2666 8GB 1.2v 1Gbx8 (0 ~ 85 °C) SAM
SQR-SD4N16G2K6SNCB	260pin SODIMM DDR4 2666 16GB 1.2v 1Gbx8 (0 ~ 85 °C) SAM

NEW



RoHS  
2002/95/EC  
CE FCC

### Features

- JEDEC standard 260-pin SODIMM
- Data transfer rate 3200 MT/s
- FIXED BOM
- Original Samsung adopted
- DRAM dynamic monitoring software support

### Specifications

Category	DDR4
Clock Speed	3200 MHz
Voltage	1.2V
Pins/DIMM	260-pin SODIMM
Gold Plating on PCB	30u"
Operating Temperature	0 ~ 85 °C
Dimensions (mm)	69.6 x 30 ± 0.13

### Ordering Information

PN	Description
SQR-SD4N4G3K2SNPCB	260pin SODIMM DDR4 3200 4GB 1.2v 512x16 (0 ~ 85 °C)
SQR-SD4N8G3K2SNBCB	260pin SODIMM DDR4 3200 8GB 1.2v 1Gbx8 (0 ~ 85 °C)
SQR-SD4N16G3K2SNCB	260pin SODIMM DDR4 3200 16GB 1.2v 1Gbx8 (0 ~ 85 °C)
SQR-SD4N32G3K2SNAB	260pin SODIMM DDR4 3200 32GB 1.2v 2Gbx8 (0 ~ 85 °C)