



FSP500-60MRB(S)

FEATURES

- Certified CB 62368-1 & CB 60950-1
- Meet 80 Plus Gold
- PMBus V1.2
- Design for 5,000 Meter above sea level
- High Reliability
- Low Ripple & Noise
- Over Current Protection
- Over Temperature Protection
- Over Voltage Protection

SAFETY STANDARD APPROVAL



DESCRIPTION

FSP500-60MRB(S) is an unique Mini-redundant power supply. It comes to offer the same form factor from 350W to 600W, and the total power capacity up to 500 Watts, plus hot swap features, which makes it to be perfectly fit in a standard 2U server chassis, and used in an industrial or home office environment. In addition, the power supply is ideally the best choice for server, workstation, communication or any other automation applications. This product also complies with the latest safety and EMC standards, which is perfectly to meet various regulations worldwide.

GENERAL SPECIFICATIONS

Dimension (L x W x H):	190 x 150 x 84 (mm) 7.49 x 5.91 x 3.3 (inch)	Environment	
Efficiency:	80 Plus Gold	Working temperature:	0°C to 50°C
Hold-up time:	115V / 60Hz: ≥ 1 ms 230V / 50Hz: ≥ 16ms	Storage temperature:	-20°C to + 80°C
Operating altitude:	5,000 meters above sea level	Working humidity:	90% RH non-condensing
		Storage humidity:	90% RH non-condensing
		MTBF:	100,000 hours of continuous operation at 25°C, Max,-output load
		Applications:	Workstation ,Storage System ,IPC Controller

INPUT SPECIFICATIONS

Input voltage:	90-264Vac
Input frequency:	47-63Hz
Input current:	115Vac @ 6A, 230Vac @ 3A

OUTPUT RATING

Outputs	+3.3V	+5V	+12V	-12V	+5Vsb	-5V
Max.	20.0A	20.0A	40.0A	0.5A	3.0A	0.3A
Min.	0.0A	0.0A	1.0A	0.0A	0.0A	0.0A
Regulation	±5%	±5%	±5%	±10%	±5%	±5%
Ripple/Noise	50 mV	50 mV	120 mV	200 mV	50 mV	200 mV

The +3.3V and +5V total output shall not exceed 130W
-5V (Optional)

MECHANICAL SPECIFICATIONS

UNIT: mm

