

# USC-365 Series

## 15.6" Ultra-Slim, All-in-One POS Computer with Intel® Core™ i3-1115G4E/i5-1145G7E Processor and P-CAP Touch Control



### Features

- 15.6" Full HD LCD (LED backlight) with P-CAP touch control
- Ultra-thin design with narrow bezel (11 mm/0.43 in)
- 11th generation Intel® Core™ i processor
- Anodized aluminum rear cover
- IP65-rated front panel for water and dust resistance
- Low-power, fanless operation without ventilation vents

### Introduction

The USC-365 all-in-one service computer is the latest addition to Advantech's USC product family and Avalo solution offerings. Powered by an Intel® Core™ i3-1115G4E/i5-1145G7E processor that delivers high-performance computing, USC-365 computers feature an ultra-slim form factor and aluminum enclosure to ensure easy installation in diverse environments.

In addition to the 15.6" TFT LCD monitor with IP65-rated front panel that protects against water and dust ingress, USC-365 can be equipped with an optional secondary display for broadcasting product promotions and increasing consumer engagement. Overall, USC-365 computers provide flexible point-of-service (POS) computing solutions that enable retailers and service staff to optimize operations and improve customer service.

### Specifications

Model	USC-365	
Processor	11th Gen Intel Core i3-1115G4E / i5-1145G7E	
Memory	1 x 260-pin SODIMM DDR4-3200 (up to 32 Gb)	
Storage	1 x M.2 SSD	
Display	15.6" TFT LCD (1920 x 1080) with AG coating, 350 cd/m <sup>2</sup> brightness	
Touch Screen	Projected capacitive (P-CAP) touch control (flat glass)	
Bus Expansion	1 x M.2 slot (for Wi-Fi and Bluetooth)	
Power Supply	65W via power adapter	
USB	3 x USB-C (One for DP, one for DC in, one for IO Hub), 2 x USB 3.0, 1 x USB 2.0 (broadside)	
Ethernet	1 x RJ-45 Intel Gigabit Ethernet (10/100/1000), I219LM	
Cash Drawer	1 x 12 V <sub>DC</sub> default, 20 V <sub>DC</sub> available upon request	
USB-C Input	20 V <sub>DC</sub>	
IP rating	IP65 for front panel	
Dimensions (W x H x D)	371 x 220 x 26.5 mm/14.6 x 8.66 x 1.04 in	
Weight	4.5 kg/9.92 lb (net); 5 kg/11.02 lb (gross)	
Operating Temperature	0 ~ 40 °C/32 ~ 104 °F	
Relative Humidity	95%RH Max @40 °C non-condensing	
Shock	10G peak acceleration (11 ms duration)	
Vibration	5 ~ 500 Hz 0.5 Grms, random	
Certification	BSMI, CE, CCC, UL, CB, FCC	
Operating System	Windows 10 IoT Enterprise	
I/O on extension HUB	UP36 Power USB Hub: 2 x COM, 3 x 12V Power USB, 1 x 24V Power USB, 2 x USB 2.0, 1 x USB C, 1 x DC IN (powered by 180W adapter) UP37 COM Port Hub: 4 x COM (RJ-48 connector), 1 x USB C Input, 6 x USB 2.0 (powered by USC-360 65W adapter)	
DeviceOn/iService Remote Device Management Software	Operating System	Windows 10
	Common Controls (Reboot, Shutdown)	✓
	Remote Desktop	✓(VNC)
	Audio Controls	✓
	Connection Status	✓
	Hardware Status	✓
	Hard Disk Status	✓
	Batch Operation Support	✓
	OTA Storage Management	FTP
	OTA Software Updates	✓
	Software Watchlist	✓
	Software Start/Stop	✓
	Peripherals Watchlist	✓


## Features Highlights



Connect hub to stand, supports separate operation



Integrate devices via USB-C



Supports wall and VESA mounting

## Dimensions

Unit: mm



## Ordering Information

Part Number	Description
USC-365HP-SI330	15.6" FHD, Pcap, AG coating, TGR-L i3-1115G4E, 8G RAM, 256G SSD, Adapter, Silvery, MSR, Stand
USC-365HP-SI530	15.6" FHD, Pcap, AG coating, TGR-L i5-1145G7E, 8G RAM, 256G SSD, Adapter, Silvery, MSR, Stand

## POS Peripherals

Part Number	Description
USC-M10G-STC03	10.1" monitor, Glass, Silver, Stand, 60cm USB-C Cbl
USC-P06-H01	USC-300 series extension hub (2COM; 4Power USB)
USC-P06-H02	USC-300 series extension hub (4COM; 6USB)
XUSC365-ADP180WBB	ADP A/D 100-240V 180W 24V POWER DIN 4PIN (Powered for USC-P06-H01+USC-365 series)

## Installation Accessories

Part Number	Description
EWM-W159M201E	new M.2 2230 WiFi5+BT5.0 module, support IEEE 802.11a/b/g/n/ac, 2.4GHz and 5GHz band channels, Support Bluetooth 5.0 system
96CB-POWER-B-1.8MB	Power cable 3P, CCC, 10A, 250V, 180 cm (China)
1700001524	Power cable 3P, UL, 10A, 125V, 180 cm (US, TW)
170203183C	Power cable 3P, 10A, 250V, 183 cm (EU)
1700018553	Power cable 3P, SAA, 2.5A, 250V, 183 cm (Australia)
1700025113-11	Power cable, ISI, 3P, 2.5A, 250V, 180 cm (India)
1700018409	Power cable, KCC, 2P, 2.5A, 250V, 183 cm (Korea, Russia)
170203180A	Power cable, BSI, 3P, 2.5A, 250V, 183 cm (UK)
1700008921	Power cable, PSE, 3P, 7A, 125V, 180 cm (Japan)
YA5C180001-17	Ant WIFI D.B 2.4+5G MHF4/0.81 GRY L110mm for 365

## Operating System

Part Number	Description
20708WLV1S0007	Img WIN11 LTSC 24H2-VLF USC-365 V1.00 7MUI (I5&I3)
20708WX1VS0015	Img WIN10 LTSC 2021-VLF USC365 x64 V1.00 7MUI

## I/O Layout

