

15.6" Ubiquitous Touch Computer UTC-515D with Intel® Celeron J1900 UTC-515F with Intel® Core™ i3-6100U



Features

- Low power and fanless system design
- Built-in Intel® Celeron J1900 (UTC-515D)
- Build-in Intel® Core™ i3-6100U (UTC-515F)
- 15.6" monitor with 16:9 widescreen display
- IP65-rated front panel for water and dust resistance
- All in one aluminum extrusion design
- Supports both landscape and portrait screen orientations
- VESA 100 mm standard mounting holes for varied mounting demands
- Side groove design for flexible peripheral installation
- Support DeviceOn/iService software for remote device management (UTC-515D/F only)



Introduction

UTC-515 features an all-in-one computing system equipped with wide format, touch based LCD panel. It is eas to integrate key peripherals and display systems for diversified self-service and interactive signage deploy in different application areas. The systems deliver updated information, with well designed interactive interfaces, fully ensure relevant content and targeted promotions are delivered. UTC series touch panel computers are the best investments to enhance user satisfaction, further brand equity, and maximize business profits. Moreover, Advantech DeviceOn/iService Software is a next-generation unified device management unified device management solution based on the WISE-DeviceOn platform. With support for batch operations and multi-device control, DeviceOn/iService enables easy device configure and deployment for convenient remote device management.


Specifications

specification	3		
Model		UTC-515D	UTC-515F
	CPU	Intel® Celeror J1900 (JTr -515D)	Intel® Core™ i3-6100U (UTC-515F) Intel® Core™ i5-6300U (Available)* Intel® Core™ i7-6600U (Available)*
	Base Frequency	2 GHz (\Puad-Co \range)	2.3 GHz (i3-6100U/Dual-Core)
	Cache	L2 Cache ?MB	L3 Cache 3MB
	Memory	1 x SO-DIN M DDR3L 1333 MHz up to 8 GB	2 x 204 pin SO-DIMM DDR3L 1600 MHz up to 16GB
	HDD	1 x 2.5 internal SATA HDD bay	
	Network (LAN)	2 Gigabit Ethernet ports (Supports Wake on LAN)	
Processor System	I/O ports	2 x RS-232 COM (RS-422/485)* 3 x USB 2.0 / 1 x USB 3.0 2 x Gigabit Ethernet (RJ-45) 1 x VGA 1 x HDMI Audio Line-out x 1, Mic-in x 1	2 x RS-232 COM (RS-422/485)* 2 x USB 2.0/ 2 x USB 3.0 2 x Gigabit Ethernet (RJ-45) 1 x VGA 1 x HDMI Audio Line-out x 1, Mic-in x 1
	Stereo Spcn er	1 W x 2	
	Bus expansion	Full-size MiniPCle / mSATA	
	Mounting	VESA 100 x 100 mm	
	Dimensions (W x H x D)	389.81 x 240.12 x 45.20 (mm)	
	Weight	4.85 kg (10.67 lb)	
OS Support		Win 10 IoT Enterprise Android 6 Linux Ubuntu 14.04	Win 10 IoT Enterprise Linux Ubuntu 20.04
	Operating Temperature	0 ~ 40° C (32 ~ 104° F)	·
	Relative Humidity	10 ~ 95% @ 40° C non-condensing	
	Vibration	0.5G	
Environmental Specifications	Shock	5G peak acceleration (11 msec. duration)	
	Certification	CE (RED Compliance), EN 61000-6-2: 2005 / AC: 2005, FCC, CB, UL, CCC, BSMI	CE (RED Compliance), EN 61000-6-2: 2005 / AC: 2005, FCC, CB, UL, CCC, BSMI
	Front Panel Protection	IP65/ NEMA4 Compliant	
	Input Voltage	12V _{DC}	
Power Supply	Power consumption	Typical 35W Max. 40W	Typical 40W Max. 50W
	Adapter	12V/5A (60W ITP Adapter)	
	Size/Type	15.6" TFT LCD with LED backlight	
	Max.Resolution	1366 x 768 (FHD 1920 x 1080 Optional)	
LCD Display	Max. Color	16.7M	
200 Diopiay	Pixel Pitch (um)	252 x 252	
	Brightness (cd/m²)	400	
	View Angle	170°/160°	
Touch Screen Option	Туре	Projected Capacitive. Analog Resistive 5-wires	
(PE/RE/GE)	Light Transmission	90% ± 2% / 80% ± 5% / 90%	
, , ,	Controller	USB Interface / USB Interface / -	

Specifications (Cont.)

	Operating System	Windows 10
	Common Controls (Reboot, Shutdown)	\checkmark
	Remote desktop	✓ (VNC)
	Audio Controls	√ *
	Connection Status	✓
DeviceOn/iService	Hardware Status	√ *
Remote Device Management (UTC-515D/F only)	Hard Disk Status	√ *
(010 0100/1 01119)	Batch Operation Support	✓
	OTA Storage Management	FTP
	OTA Software Updates	✓
	Software Watchlist	✓
Dependant on device model	Software Start/Stop	√

Note: DeviceOn/iService software must be downloaded from the Advantech website at https://www.advantech.com/search/?q=DeviceOn%2FiServi_x_&st=support&sst=Utility



Ordering Information

Part No.	Description
UTC-515D-PE	15.6" 9H PCT.T/S with Intel Celeron J1900, 4GB RAM, IT Adapter
UTC-515DP-ATB0E	15.6" 7H PCT.T/S with Intel Celeron J1900, 4GB RAM, IT Adapter
UTC-515D-RE	15.6" Resi.T/S with Intel Celeron J1900, 4GB RAM, IT Adapter
UTC-515F-PE	15.6" 9H PCT.T/S with Intel Core i3-6100U, 4GB RAM, IT Adapter
UTC-515FP-ATB0E	15.6" 7H PCT.T/S with Intel Core i3-6100U, 4GB RAM, IT Adapter
UTC-515FR-ATB0E	15.6" Resi.T/S with Intel Core i3-6100U, 4GB RAM, IT Adapter
1702002605	Power cord 2P FRANCE 10A/16A 220V 1.83M 90D
1702002600	Power Cord 3P UL/CSA(USA) 125V 10A 1.83M 180D
1700000596	Power Cord (China) CCC,10A 250V, 3P 1830mm
1700018704	Power Cord UK BSI 2P 10A 250V 180cm 18AWG
1960060674N001	IO Cover for UTC-515 series

Peripherals for UTC-500 series

Part No.	Description
UTC-P01-A1E	5M Camera Module For UTC-5XX (USB connection)
UTC-P02-A0E	Magnet Strip Reader For UTC-5XX (USB connection)
UTC-P03-A1E	RFID Reader For UTC-5XX (USB connection)
UTC-P06-A2E	Smart Card Reader For UTC-5XX (USB connection)
UTC-P07-A4E	2D Barcode Module (Honeywell) for UTC-500 Series (USB connection)
UTC-P09-A0E	Fingerprint reader for UTC-5xx (USB connection)
UTC-P21-A3E	2D Barcode reader + RFID + SCR


Installation Accessory

	Part No.	Description
	96PD-00824	UTK-700 Desktop Stand (w/o Printer)
	96PD-00825	UTK-700 Extension Tower (For 96PD-00824 on v)
	UTC-520-STAND1E	Desktop stand for UTC-515/520
	UTC-T01-STAND	Triangle shape floor stand
	UTC-H01-STANDE	H-shaped floor stand
	ARES-2424X-S170201	Table Stand,100x100/75x75
	ARES-12250-L101000	Wall Mount, 75/100mm

UTC-515 WiFi Ordering Information

Part No.	Description
UTC-WIFI-A0E	EWM-W135H01E, 9(2.11 a/b/g/n,AR9382,2T2R, HMC
UTC-WIFI-A1E	EWM-W168H01E, 802 11ac/a/b/g/n, 2T2R, BT4.2, HMC
UTC-WIFI-A2E	EWM-W189H02E, 802.11ac/a/b/g/n, 2T2R, BT4.2, HMC
UTC-WIFI-A3E	EWM-W193H01E, 802.11ac/a/b/g/n, 2T2R, BT5.0, HMC

Fully- Integrated 1/4



.^ Pu wer switch ? Arnenna Port C Line-out

D. Mic-in

E. COM2 F. COM1 G. USB 3.0 x 2, USB 2.0 x 2 (UTC-515E/F) USB 3.0 x 1, USB 2.0 x 3 (UTC-515D)

H. HDMI

I. VGA

J. LAN Ports x 2

K. DC Input

DeviceOn/iService

Unified Remote Device Management Software



Features

- Supports Advantech devices equipped with Windows, Android, and Linux OS
- Flexible device, location, user, and permissions management
- Enables remote monitoring and control of hardware, software, and peripherals
- Supports over-the-air (OTA) firmware and software updates
- Ensures quick, easy, and secure device onboarding
- RESTful APIs for third-party system integration

Introduction

Advantech's DeviceOn/iService is a next-generation unified device management solution based on the WISE-De in Juliform. Designed to enable centralized monitoring and remote management, DeviceOn/iService supports Advantech devices equipped with Windows, Linux, or And pict prevaing systems. The software also supports the management of applications and integrated peripherals, such as a barcode scanner, card reader, camera, and printer. User to a remotely access and control connected devices, take screenshots, rollout OTA upgrades, and use remote desktop capabilities for troubleshooting from any location at any time. Moreover, DeviceOn/iService supports batch operations to facilitate the management of multiple devices simultaneously for easy and convenient device configuration and lend ment.

Remote Access

Total Management



Devices & Hardware

- Windows, Linux, Android
- Hardware, storage, battery

Software & Peripherals

- Software monitoring & access
- Screens, USB devices, proters

Remote Controls

- Power controls
- Audio, backlight controls

Real-Time Monitoring

Connection/hardware status

Software/peripheral status

Failure notifications

Software controls



Operational Efficiency



- File repository management
- App store



Batch Controls

- 1-to-many batch reboot, etc.
- Time-saving tasks



Open for Expansion

- Peripheral integration
- Open APIs for integration



Troubleshooting

- Screenshots
- Remote desktop support



Setup Booster

- Software/peripheral watchlist
- Roles, rule templates

Note: Some functions may vary according to the product

System Architecture

